TRIME®
Lighting Towers

LED TECHNOLOGY

7000 sqm

Illuminated area

Self-sufficient engine powered unit

Operation: **ENGINE**
Engine **Kubota Z482E**

X-START
4x400W LED - 8,5M

X-START

4x400W LED - 8,5M

FEATURES

- Multi-directionally adjustable and tiltable floodlights
- 7 sections vertical tower 8,5 m, 340° rotatable
- Galvanized metalworks
- 80 µm powder coating
- Central lifting eye, forklift pockets for effective handling
- Plug & play, colour coded cables and connectors
- Guided main coiled cable to avoid damage during tower operation
- Control panel alarms for engine protection and fuel level indicator
- Circuit breaker for electrical protection against overload
- External emergency stop button
- Certified wind stability up to 80 km/h
- 5 height adjustable stabilizers
- On board levels for guidance during stabilization





Dimension & weight	Dimension min (mm)	Dimensions max (mm)	Roughly weight (Kg)
	1830x1370x2560 (LxWxH)	2320x2570x8500 (LxWxH)	750

Floodlights	Type	Power (each)	Floodlights number	IP level	Illuminated Area (sqm)
	LED	400W	4	67	6084

Mast	Lifting Method	Max Height	Max Wind Speed	Rotation
	Hydraulic	8,5 m	80 km/h	340°

Alternator	Model	Rated Output	Voltage	Degree of protection
	Synchronous	3.5 kVA-50Hz	230V	IP 23

Engine	Model	rpm	Tank capacity	Fuel consumption
	Kubota Z482E, 2-cylinders	1500	80 L	0.55 l/h

The company reserves the right to modify the technical specifications, items and design without notice.
The images of the products are indicative for illustrative purposes only.

TRIME® Lighting Towers

Sales Dept. +39 0382 406 252
www.trime.it - info@trime.it